

Mustang

Floor Machine



For a durable, powerful floor machine in an economical package, choose the Mustang. Precision balanced for easy operation and maneuverability, this machine scrubs, strips, spray buffs, polishes, and shampoos.

- The Mustang features a straight line planetary gear system that provides efficient transfer of power from the motor to the pad driver. This design ensures years of trouble-free operation.
- A mechanical lock-out on the handle must be released before the switch lever on the Mustang will activate. This special safety mechanism helps prevent unauthorized operation when the machine is unattended.
- The Mustang is ideal for schools, office buildings and other facilities where appearances need to be kept up while holding equipment costs down.
- The Mustang comes with either a 1 HP or 1.5 HP 66-frame motor, and is available in 17 and 20-inch widths.



NSS Enterprises, Inc.
3115 Frenchmens Road
Toledo, Ohio 43607-2958
USA
www.nss.com

Mustang Specifications

Pad Size	17 in. (43 cm) 20 in. (51 cm)	Cord -120V. -240V.	Safety yellow 50 ft. (15.2 m) 14-3 ST 75 ft. (23 m) 16-3 ST
Motor -HP -Speed -Type -Voltage	1 HP or 1.5 HP 1700 RPM 66 frame, dual capacitor 110-120V., 220-240V. available	Weight -Machine • 17-in. 1 HP • 20-in. 1 HP • 17-in. 1.5 HP • 20-in. 1.5 HP -Shipping • 17-in. 1 HP • 20-in. 1 HP • 17-in. 1.5 HP • 20-in. 1.5 HP	93 lbs. (42.2 kg) 107 lbs. (48.6 kg) 100 lbs. (45.4 kg) 114 lbs. (51.8 kg) 112 lbs. (50.8 kg) 126 lbs. (57.2 kg) 119 lbs. (54 kg) 133 lbs. (60.4 kg)
Current -1 HP -1.5 HP	12.6 amps @ 120V 6.8 amps @ 240V 15 amps @ 120V 8.3 amps @ 240V	Warranty	3 year limited
Gearbox -1 HP -1.5 HP	2-idler planetary with 11:1 ratio 3-idler planetary with 11:1 ratio		

Productivity — Measured in square feet per hour.

	Polish	Scrub	Shampoo	Spray Buff
Mustang 17 in.	4,400	2,700	1,200	1,900
Mustang 20 in.	6,000	3,600	1,430	2,100



The Mustang features a mechanical lock-out on the handle, which must be released before the switch lever can be activated. This important safety mechanism helps deter unauthorized operation when the machine is unattended.

1 Metal cord strain relief and internal compression lock prevent the cord from being pulled out of the machine.

2 Sturdy 1.5-in. tube handle is chrome-plated to resist corrosion.

3 360° non-marking bumper protects walls and fixtures from accidental damage.

5 Dual switch levers allow the operator to easily control the side-to-side movement of the machine.

4 5-in. rear transport wheels make the Mustang easy to move to the job site.



NSS® Enterprises, Inc.
3115 Frenchmens Road
Toledo, Ohio 43607-2958 USA
419/531-2121 Fax 419/531-3761
www.nss.com
mailus@nss.com
Specifications and appearance
subject to change without notice.

DISTRIBUTED BY